



1982-2022
Aniversario
Estatuto de
Autonomía de
Aragón



Plan de Recuperación,
Transformación
y Resiliencia



Financiado por
la Unión Europea
NextGenerationEU



Universidad
Zaragoza

Axion Physics in PPCC: IAXO

1ST MEETING ARAGÓN - COMUNIDAD VALENCIANA OF THE ASTRO-HEP COMPLEMENTARY PLANS
GLORIA LUZÓN (CAPA) ON BEHALF OF IAXO-ZARAGOZA

Subprojects in LA5



LA5.1	Integration of the ultra-low background detection line of the axion helioscope BabyIAXO, and study of the extension of the physics case to the detection of Dark matter axions (RADES)	UNIZAR-ITA
LA5.2	Implementation of improvements in energy threshold and noise background of the experiment TREX-DM for the search of low mass WIMPs at the LSC	UNIZAR-ITA
LA5.3	ANALIS+: improvements in the sensitivity of ANALIS-112 using automatic learning and a new experimental approach	UNIZAR

Milestone H5.1.1 – Prototype detection line, and shielding built and in operation



International Axion Observatory



A fourth-generation axion helioscope




BabyLAXO



Collaboration created in 2017: ~100 scientists from 21 institutes, 4 Spanish (CAPA, CEFCA, ICCUB, UPCT)

Helioscope generations




- Currently under construction at DESY
- Test and improve all systems. Risk mitigation for full IAXO
- **Magnet:** 2 bores of $\phi = 70$ cm, $L = 10$ m, $B = 3-4$ T
 - test design options of final IAXO magnet
- **Dedicated x-ray optics:** 0.2 cm^2 focal spot
- **Detection lines** representative of final ones
 - Micromegas baseline
- **Toroidal magnet:** 8 bores of $\phi = 60$ cm, $L = 20$ m, $B = 5.4$ T
- **Dedicated x-ray optics:** 0.2 cm^2 focal spot
- **Tracking system:**
 - based on CTA
 - 50% Sun-tracking time
- **8 detection lines**


[Abeln, A., et al. "Conceptual design of BabylAXO, the intermediate stage towards the International Axion Observatory." *Journal of High Energy Physics* 2021.5 \(2021\): 1-80.](#)

Sensitivity and physics potential

Further physics potential



Non-primakoff solar axions




DM axions: haloscope setups in
(Baby)IAXO




Axions from close-by Supernovae

Physics
studies in
PPCC



X-ray detector requirements


- High X-ray detection efficiency in the ROI (0-10 keV)
- Ultra low background levels:
 - 10^{-7} c/keV/cm²/s (BabyIAXO)
 - 10^{-8} c/keV/cm²/s (IAXO)



Microbulk Micromegas
TPC
(U. Zaragoza and
CEA-Saclay)




GridPix TPC
(U. Bonn)




SDD: Silicon Drift
Detectors
(Technical U. Munich)

IDEALLY

- Low energy threshold (100 eV)
- Good energy resolution



MMC: Metallic Magnetic
Calorimeters
(U. Heildeberg and
CEA-Saclay)






TES: Transition Edge
Sensors
(U. Zaragoza-INMA
ICMAB-CSIC IJCLab)

Goals in PPCC

- 1. Construction of the X-ray detection lines of the experiment based on Micromegas detectors**, according to the results obtained from the prototypes built so far, and their integration into the overall structure of the experiment.
- 2. Implementation of new strategies to reduce the background of the Micromegas detectors for BabyIAXO**, based on the results obtained with the IAXODO and D1 prototypes (the latter at the LSC), including:
 - a) Increase in the efficiency of the active shielding, with the implementation of new veto concepts for cosmic events.
 - b) Electromagnetic study and characterization at the LSC of the site of the IAXO-D1 prototype.
 - c) Analysis of the electrical/electronic architecture of the data acquisition (DAQ) and control system; implications and improvements for electromagnetic noise reduction according to EMI/EMC criteria.
 - d) Implementation of a new, more radiopure acquisition electronics system.
 - e) Implementation of an in-situ calibration system based on X-ray fluorescence generation using a UV lamp.

H1-The beamlines at BabyLAXO Experiment




Approved and launched the purchase order of the 2 large-dimension stainless steel vacuum lines for installation between the X-ray optics and the particle detectors of the babyLAXO Experiment → To be delivered by the end of the 2025

Background reduction: Micromegas prototypes

Zaragoza

Surface level

- Effect of multi-layer veto system to tag cosmogenic neutrons (in addition to muons)
- 20cm lead+veto



Laboratorio Subterráneo
de Canfranc

- Cosmic muon flux reduced by a factor 10^4 : intrinsic detector background
- Test of different gas mixtures : Ar or Xe/Ne
- 20 cm lead
- Buffer gas to reduce Rn contamination



IAXO-D1@IAXOLAB

Passive shielding (lead): 20 cm

Active shielding: partially mounted+ TCM (Trigger Clock Module) to synchronize MM- veto triggers installed



%Ar+2%Isobutane with passive shielding:
 $[3-4] \times 10^{-6} \text{c/keV/cm}^2/\text{s}$

IAXO-D0 After veto cuts $(8.56 \pm 1.22) \times 10^{-7} \text{c/keV/cm}^2/\text{s}$

K. Altenmuller et al., Background discrimination with a Micromegas detector prototype and veto system for BabylAIXO, Front. in Phys. 12 (2024) 1384415 [2403.06316]

IAXO-D1 at the LSC: background status

Argon background level $[1-2] \times 10^{-7}$ counts/keV·cm 2 ·s

- Lowest background level achieved with this technology underground

Xenon background level $[5-6] \times 10^{-7}$ counts/keV·cm 2 ·s


- Not compatible with previous measurements in Ar+Iso at the LSC

^{222}Rn contamination from filters

Altenmüller, K., et al. 2021 IEEE Nuclear Science Symposium and Medical Imaging Conference (NSS/MIC). IEEE, 2021.



1. Low gain run with Xe confirmed Rn contamination
2. Ar recirculating: compatible background level



HENSA collaboration

A. Quero
presentation@CPAN XVI
Madrid 2024

- Collaboration with the dark matter search experiment (Baby) IAXO (March - 2024)

<https://gifna.unizar.es/iaxo/>

- Neutrons above ~ 20 MeV contribute to the interest region of their detectors




Outdoor measurement: HENSA + IAXO team

- **Objective:** Characterization of the neutron **background spectrum** and the **moderation effect** of their laboratory in quiet solar conditions



(Baby) IAXO laboratory measurement

- Unfolding with the “POU” code that we are developing.
- Reduction of ~50% on the evaporation and high energy components of the spectrum.
- The thermal component is almost constant.
- Next step: DESY, Germany.



Magnitude	[20 MeV, 1 GeV]	(1 GeV, 100 GeV]	Total
Indoor Fluence ($\text{cm}^{-2}\text{h}^{-1}$)	$8.2^{+0.8}_{-1.2}$	$0.15^{+0.09}_{-0.07}$	$26.8^{+0.5}_{-0.8}$
Outdoor Fluence ($\text{cm}^{-2}\text{h}^{-1}$)	$17.9^{+1.3}_{-2.3}$	$0.39^{+0.18}_{-0.13}$	$49^{+1.0}_{-1.5}$
Decrement (%)	-54.19	-61.54	-45.31

HENSA++ installation (Position 1 @HERA South)




DESY 2025

- Acquiring data since 23/05/2025
- Calibrated with AmBe & Cf-252 on 26/05/2025
- We miss Detector 10 (on shipment)
- We plan to move the setup to Position 2 on Wednesday

Noise Reduction

Analysis of the electrical/electronic architecture of the data acquisition (DAQ) and control system; implications and improvements for electromagnetic noise reduction according to EMI/EMC criteria

- Noise analyse of the IAXO-D1 detector
last month at ITA installations




ITAINNOVA activities in L5



- Performance improvement studies in terms of connectivity, radiopurity and electromagnetic noise at infrastructure and system level;
 - Electromagnetic study and characterization at the LSC of the site where the IAXO experiment and TREX-DM (L2500) are relocated.
 - Analysis of the electrical/electronic architecture of the data acquisition (DAQ) and control system; implications and improvements for the reduction of electromagnetic noise according to EMI / EMC criteria.
- **Several meetings and discussions have already taken place**



L2500 characterization at
LSC – REF



Radiopure acquisition electronics system



Front End, 4 cards with STAGE and limandes to conect to Back End

Radiopure acquisition electronics system

1) Limandes Micromegas-FEC

- Produced (at UNIZAR)
- Under radiopurity measurement

2) FEC

- 16 produced and assembled (Eonica)
- FtF mechanics ready
- To be tested

3) Limandes FEC-BEC

- Produced (at UNIZAR)
- Assembly started (UB)

4) BEC

- Produced and assembled
- FPGA programmed (15+1)
- BIOS configured
- DC levels tests passed
- Link to FEC to be tested

12/03/2025

• Next steps


- Soldering connectors on limandes
- Testing
 - BEC with FEC
- Design/produce BEC heat sink
 - Using FPGA sink + fan

E. Picatoste presentation 21th IAXO
collaboration meeting March 2025





Calibration system based on X-ray fluorescence generation using a UV lamp.

X-RAY GENERATOR



Filter combination:

- Ti target + 40 μm Ti filter \rightarrow 4.5 keV peak
- Cu target + 50 μm Ni filter \rightarrow 8 keV peak
- Small hole with 100 μm Al filter \rightarrow 1.5 keV peak



Summary

- LA5.1 subproject **Integration of the ultra-low background detection line of the axion helioscope BabyLAXO**

Milestone H5.1.1 – Prototype detection line, and shielding built and in operation in progress

- Physics studies
- Prototype detection line designs and in construction to be delivered by the end of 2025
- Background reduction
 - Internal background studies including filter emanation
 - Cosmic studies including HENSA campaigns at Zaragoza and DESY
 - Shielding design
 - Radiopure electronics
- Noise reduction (ITA)
- lowering the threshold (electronics and calibration source)
- ... a lot of work